

# UJF-6042 MkII e



Tabletop UV-LED Flatbed Printer

16.5" x 24"

## Built To Streamline Your Production

This large tabletop flatbed printer brings ease and efficiency to on-demand, direct-to-object printing. More reliable than ever with improved automatic maintenance features. Its versatility provides you unlimited opportunities to print on specialty items, awards and personalized products.

- Available in 16.5" x 24"; up to 6" thick (610 x 420 x 153 mm)
- Enclosed print area reduces dust contamination and UV exposure
- Eco-friendly with low VOC, GREENGUARD Gold certified UV-LED inks
- Pair with our desktop 3D printer to produce jigs, molds for thermoforming or custom models
- Mimaki Clear Control (MCC) for smoother, cleaner clear effects
- RIP software RasterLink7 and MDL included
- 2.5D with Artista texture library support and ADA capable
- Staggered printhead arrangement enables simultaneous printing of two layers of color and spot colors, maintaining high productivity
- Connected printing capable with MDL (Mimaki Device Language) commands for automation workflows
- Includes industry leading Mimaki Core-Technologies

*For best results, always use Mimaki original inks*

# Mimaki® UJF-6042 MkII e

<b>Printhead</b>	Four on-demand piezo heads in a staggered array
<b>Print resolution</b>	Maximum: 1200 x 1200 dpi
<b>Print speed</b>	UJF-6042 MkII e – as many as 468 objects per hour*
<b>Maximum print area</b>	23.6" x 16.5" (600 x 420 mm)
<b>Maximum thickness</b>	up to 6.02" (153 mm)
<b>Maximum Media weight</b>	17.1 lbs. (8.0 kg)
<b>Ink Type/Color</b>	LH-100 UV: C, M, Y, K, Lc, Lm, W, Clear LUS-120 UV: C, M, Y, K, Lc, Lm, W, Clear LUS-150 UV: C, M, Y, K, W PR-200 UV Primer
<b>Ink Package size</b>	1 liter & 250 ml bottles* standard (*LH-100 & LUS-120 only)
<b>Flatbed table</b>	Single-zone, pin register, jig compatible vacuum table High precision ball screw mechanism assists with accurate table movement
<b>Certifications</b>	VCCI class A / FCC class A / ETL IEC 62368-1 CE Marking (EMC, Low voltage, Machinery directive, and RoHS) CB / REACH / Energy Star / EAC / RCM
<b>Interface</b>	Ethernet 1000BASE-T USB2.0 Hi-speed
<b>Power supply</b>	Single-phase AC100-240V, ±10%, 50/60Hz ±1Hz
<b>Operational environment</b>	Temperature 68° – 86° F (20-30° C) Humidity: 35–65 % RH (Non condensing)
<b>Dimensions (W x D x H)</b>	65.6" x 50.8" x 33.7" (166.6 x 129 x 85.6 cm)
<b>Weight</b>	330.7 lbs. (150 kg)

Tabletop UV-LED Flatbed Printer

16.5" x 24"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
150-A Satellite Blvd NE, Suwanee, GA 30024

\*Production print speeds based on a UJF-6042 MkII e table filled uniformly with objects similar in size to a SanDisk Extreme External SSD. Production speeds are not guaranteed and may vary.

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2022, Mimaki USA, Inc.

Rev. 11/8/21